

Flat Festoon Cable

- Conductor** Bare extra flexible soft annealed copper
- Insulation** Colour coded PVC
- Jacket** Yellow PVC
- Temperature** -40°C to +105°C
- Voltage** 600V
- Applications** Designed for overhead cranes, hoists, monorails and other industrial applications.
- Approvals** CSA, UL
- Packaging** 300m spools, Long length Reels cut to length.
- Colour Code** Nema standard (Chart 17)



Product Code	AWG Size	# of Cond.	Cond. Strand	AMPS* Continuous Duty Rating at 30C Ambient	Amps Short Time Rating 60 Min.	Amps Short Time Rating 30 Min.	Nom. O.D. (Inches)	Ship. Weight lbs/mft
12U1608	16	8	65	15	N/A	N/A	.222 x 1.180	180
12U1612	16	12	65	15	N/A	N/A	.225 x 1.680	280
12U1404	14	4	41	25	31	32	.280 x 0.690	120
12U1408	14	8	41	17	N/A	N/A	.280 x 1.280	180
12U1412	14	12	41	17	N/A	N/A	.225 x 1.820	340
12U1204	12	4	65	30	36	40	.250 x .0800	120
12U1207	12	7	65	21	N/A	N/A	.280 x 1.250	290
12U1208	12	8	65	20	N/A	N/A	.280 x 1.400	310
12U1004	10	4	105	40	49	52	.276 x 0.880	240
12U0804	8	4	168	50	63	69	.360 x 1.230	450
12U0604	6	4	266	75	83	94	.470 x 1.505	580
12U0404	4	4	420	95	111	130	.550 x 1.720	750
12U0204	2	4	665	130	148	173	.580 x 2.020	950

*Ampacities (Amps per conductor) are based on 30°C ambient temperature in air, 90°C conductor temperature.