NSPEC CAT 6-CMP (250MHZ) PLENUM

Description	NSPEC Cat 6 PLENUM offers unbeatable value, as this fully TIA/EIA 568-B.2-1-compliant cable comes at a very practical price. NSPEC Cat 6 is meter-marked for easy measuring and comes in a durable box with special features for fast and effortless installation.
Conductor	Solid bare copper
Insulation	Fluorinated Ethylene Polymer (FEP)
Jacket	Flame Retardant, Low Smoke PVC
Compliance	UL Verified to Category 6, UL 444, UL Listed CMP (NFPA 262), ISO/IEC 11801, ANSI/TIA/EIA 568-B.2-1, ANSI/TIA 568-C.2, ANSI/ICEA S-90-661-2002, RoHS Compliant
Applications	10BASE-T through 1000BASE-T Ethernet ATM and token ring

Product Code	AWG Size	Pair Count	Nom Diameter in (mm)	Nom Impedance (ohms)	Nom Velocity of Prop. (%)	Approx Weight lbs/kft (kg/km)	Jacket Colour
426U10	23	4	0.22(5.6)	100± 15	71	25(37)	White
426U40	23	4	0.22(5.6)	100± 15	71	25(37)	Blue
426U50	23	4	0.22(5.6)	100± 15	71	25(37)	Yellow

Cat6_CMP2.pdf