


RG6U - Quad Aluminum Armoured

- Jacket** Inner and outer PVC jacket
- Voltage** 300V
- Armour** Aluminum Interlocked Armour
- Temperature** -30°C to 75°C
- Approvals** CSA Type CMG, HL
- Applications** Suitable for indoor and outdoor applications, including direct burial.



| Product Code | AWG Size | Strand & Cond. | Shield/Coverage | Insulation Material & Diameter (in.) | Nom. OD (in) | Nom. Vel. of Prop. | Nom. Cap. (pF/ft) | Rating | Cable Weight (lbs/mft) | Nominal Attenuation | |
|--------------|----------|----------------|------------------------|--------------------------------------|--------------|--------------------|-------------------|---------|------------------------|---------------------|----------|
| | | | | | | | | | | mHz | Db/100ft |
| 36123092A | 18 | Solid BCCS | 2 Foil 2 Alum Braid | FPE 0.180 | 0.60 | 82% | 16.2 | CSA/FT4 | 142 | 50 | 1.37 |
| | | | | | | | | | | 100 | 1.97 |
| | | | | | | | | | | 200 | 2.82 |
| | | | | | | | | | | 300 | 3.48 |
| | | | | | | | | | | 400 | 4.04 |

RGU_QAA.pdf