

SJTOOW Service Cord

Conductor 18 through 6 AWG fully annealed stranded bare copper

Insulation Thermoplastic Elastomer

Jacket Ultra Flex® Thermoplastic Elastomer, black, white or yellow

Temperature -50°C to +105°C

Voltage 300V

Applications Indoor applications for portable power tools, industrial and consumer lighting fixtures, office equipment power supplies, construction site power, and industrial and floor care equipment

Approvals CSA C22.2 No. 49 FT1/FT2, UL-62, ROHS Compliant, MSHA Approved

Packaging 250' (76.2 m), 1000' (304.8 m) reels

Colour Code 2c - Black, White 3c - Black, White, Green 4c - Black, White, Red, Green
*Green Conductor used for grounding purposes only



Product	AWG Size	# of Cond.	Cond. Strand	Nom. Insul. Thickness (Inches)	Nom. O.D. (Inches)	AMPS*	Ship. Weight lbs/mft
12COO1804	18	4	16/30	0.030	0.340	7	65
12COO1803	18	3	16/30	0.030	0.310	10	55
12COO1603	16	3	26/30	0.030	0.338	13	70
12COO1602	16	2	26/30	0.030	0.319	13	55
12COO1403-10	14	3	41/30	0.030	0.372	18	90
12COO1203-10	12	3	65/30	0.030	0.443	25	130

SJTOOW_SC.pdf