TR64 Hookup Wire

Conductor	Solid annealed tinned copper
Insulation	Colour coded PVC
Voltage	600V
Temperature	-20C to +90C CSA , STYLE 1007 80C or 1569 105C
Applications	Internal wiring of electrical and electronic equipment, panels and meters.
Approvals	CSA C22.2 No. 127 FT1 Vertical Flame Test, UL AWM subject 758 VW-1
Packaging	75m, 150m & 300m spools, long length reels.

Product Code	AWG Size	Cond. Strand	Nom. Insul. Thickness inches	Suggested Working Voltage	Nom. O.D. inches	Ship. Weight lbs/mft
34H2601	26	SOLID	.015	300	.047	2
34H2401	24	SOLID	.015	300	.052	3
34H2201	22	SOLID	.015	300	.057	4
34H2001	20	SOLID	.015	300	.064	5
34H1801	18	SOLID	.015	300	.072	7
34H1601	16	SOLID	.015	300	.083	10
34H2607	26	7	.015	300	.050	2
34H2407	24	7	.015	300	.056	3
34H2207	22	7	.015	300	.062	4
34H2010	20	10	.015	300	.070	5
34H1816	18	16	.015	300	.079	7
34H1626	16	26	.015	300	.092	10