

# Flat Festoon Cable

**Conductor** Bare extra flexible soft annealed copper  
**Insulation** Colour coded PVC  
**Jacket** Yellow PVC  
**Temperature** -40°C to +105°C  
**Voltage** 600V  
**Applications** Designed for overhead cranes, hoists, monorails and other industrial applications.  
**Approvals** CSA, UL  
**Packaging** 300m spools, Long length Reels cut to length.  
**Colour Code** Nema standard



Product Code	Cond. Size	# of Cond.	Cond. Strand	AMPS* Continuous Duty Rating at 30C Ambient	Amps Short Time Rating 60 Min.	Amps Short Time Rating 30 Min.	Nom. O.D. (Inches)	Ship. Weight lbs/mft
15B1608	16	8	65	15	N/A	N/A	.222 x 1.180	180
15B1612	16	12	65	15	N/A	N/A	.225 x 1.680	280
15B1404	14	4	41	25	31	32	.280 x 0.690	120
15B1408	14	8	41	17	N/A	N/A	.280 x 1.280	180
15B1412	14	12	41	17	N/A	N/A	.225 x 1.820	340
15B1204	12	4	65	30	36	40	.250 x .0800	120
15B1207	12	7	65	21	N/A	N/A	.280 x 1.250	290
15B1208	12	8	65	20	N/A	N/A	.280 x 1.400	310
15B1004	10	4	105	40	49	52	.276 x 0.880	240
15B0804	8	4	168	50	63	69	.360 x 1.230	450
15B0604	6	4	266	75	83	94	.470 x 1.505	580
15B0404	4	4	420	95	111	130	.550 x 1.720	750
15B0204	2	4	665	130	148	173	.580 x 2.020	950

\*Ampacities (Amps per conductor) are based on 30°C ambient temperature in air, 90°C conductor temperature.